


BRIDGE WEIGHT LIMITS


PRIMARY ROADS

MAP ID	ROAD NAME	LOCATION	TONS		
			#1	#2	#3
(2)	W Beaver Rd	0.31 mile E. of S. Garfield Rd	42	74	82
(3)	E Chip Rd	0.5 mile W. of Old Beaver Rd	42	52	58
(5)	W Erickson Rd	0.6 mile W. of N. Flajole Rd	Bridge Is Closed		
(6)	Fraser St	200 feet E. of Chip Rd	18	31	33
(11)	S Mackinaw Rd	0.58 mile N. of E. North Union Rd	18	20	29
(12)	Monitor Rd	540 feet S. of Fraser St	42	64	82
(13)	Saganing Rd	0.25 mile E. of N. 9 Mile Rd	21	32	45
(14)	E Wheeler Rd	600 feet W. of S. 4 Mile Rd	42	70	77
(43)	Beaver Rd	200 feet W. of 4 Mile Rd	42	51	56

LOCAL ROADS

MAP ID	ROAD NAME	LOCATION	TONS		
			#1	#2	#3
(15)	N 8 Mile Rd	0.2 miles N. of E. Whitefeather Rd	42	64	74
(16)	N 8 Mile Rd	0.25 mile S. of W. Mount Forest Rd	32	56	71
(17)	S 8 Mile Rd	0.5 mile S. of W. Wheeler Rd	17	19	29
(18)	S 8 Mile Rd	900 feet S. of Doud Rd	23	30	50
(20)	Avalon Rd	200 feet N. of Rashotte Rd	3	3	3
(21)	Bay Midland Line Rd	75 feet S. of W. Anderson Rd	17	17	17
(22)	E Brown Rd	at S Briggs Rd	26	33	40
(23)	S Cotter Rd	0.4 mile N. of E. Munger Rd	28	35	40
(25)	N Fraser Rd	1000 feet N. of E. Neuman Rd	12	12	12
(26)	N Fraser Rd	0.32 mile S. of E. Whitefeather Rd	10	15	50
(27)	S Fraser Rd	0.25 mile S. of E. Cottage Grove Rd	27	32	53
(28)	S Fraser Rd	0.56 mile N. of E. North Union Rd	42	61	74
(29)	Hunter Rd	0.3 mile N. of E. Pinconning Rd	12	15	17
(30)	Kaiser Tower Rd	0.3 mile S. of E. Prevo Rd	4	4	4
(31)	Myers Rd	50 feet W. of S. Mackinaw Rd	16	16	16
(32)	S Nolet Rd	200 feet N. of E. Brown Rd	22	29	42
(34)	E Russell Rd	at S Briggs Rd	Bridge Is Closed		
(35)	E Russell Rd	650 feet E. of S. Cotter Rd	30	41	82
(36)	N State Rd	300 feet N. of E. Coggins Rd	11	16	18
(39)	Ziegler Rd	0.10 mile S. of M-84	42	62	82
(40)	N 9 Mile Rd	0.20 mile N. of Parish Rd	40	40	56



ALLOWABLE TRUCK LOADINGS AND DIMENSIONS Regulations Pertaining to the Operation of Trucks and Trailers According to Act 200, P. A. 1949 as Amended.					
Designated Routes		 Designated Routes & All Season Routes  Designated Routes			
TABLE OF MAXIMUM ALLOWABLE GROSS AXLE LOADINGS					
NON-LOADINGS WHEN SEASONAL LOAD LIMITATIONS ARE NOT IN FORCE				SEASONAL LOAD LIMITATIONS	
					
				35% Reduction (All Designated Routes Not All Season)	35% Reduction (On All Other Routes)
SPACING BETWEEN AXLES		On Designated Routes	On All Other Routes		
9 feet or over	18,000 lbs.	18,000 lbs.	11,700 lbs.	11,700 lbs.	
More than 3½ feet, but less than 9 feet	13,000 lbs.	13,000 lbs.	8,450 lbs.	8,450 lbs.	
When part of a tandem axle assembly	16,000 lbs.*	13,000 lbs.	10,400 lbs.*	8,450 lbs.	
When less than 3½ feet	9,000 lbs.	9,000 lbs.	5,850 lbs.	5,850 lbs.	
Maximum load on any wheel shall not exceed: (lbs. per inch of the tire width)	700 lbs.	700 lbs.	450 lbs.	450 lbs.	
* Applies to only one (1) tandem axle assembly. Each additional tandem axle assembly shall not exceed 13,000 lbs. Per axle during normal loading and 8,450 lbs. per axle during restricted loading.					
NOTE: When normal loadings are in effect on designated routes, see Michigan Vehicle Code Act 300 of 1949 section 257.722 as amended, paragraphs 2 and 3, for legal combinations of vehicles.					
Designated Routes will allow 53' trailers and all other "designated" lengths and width maximums.					

NOTE: Special Permits may be obtained from the Bay County Road Commission for one trip in and one trip out on specified sections of roads.

